



Leading Through Innovation



SOLID CARBIDE

**GENERAL
CARBIDE DRILLS**
UNIVERSELLE VHM - BOHRER

- For General Purpose, DIN 338 & DIN 6539
- Für allgemeine Anwendungen, DIN 338 & DIN 6539

SELECTION GUIDE



SERIES	D5405	D5407
STANDARD	DIN 6539	DIN 338
LENGTH	STUB	JOBBER
SIZE MIN	D1.0	D1.0
SIZE MAX	D13.0	D13.0
PAGE	A155	A157

SURFACE TREATMENT

Bright

SOLID CARBIDE GENERAL CARBIDE DRILLS

For General Purpose, DIN 338 & DIN 6539



Please visit globalyg1.com/mat for material search

◎ : Excellent ○ : Good

Recommended cutting conditions : p.A159

ISO	VDI 3323	Material Description	Composition / Structure / Heat Treatment	HB	HRc		
P	1	Non-alloy steel	About 0.15% C Annealed	125		◎	◎
	2		About 0.45% C Annealed	190	13	○	○
	3		About 0.45% C Quenched & Tempered	250	25		
	4		About 0.75% C Annealed	270	28		
	5		About 0.75% C Quenched & Tempered	300	32		
	6	Low alloy steel	Annealed	180	10	○	○
	7		Quenched & Tempered	275	29		
	8		Quenched & Tempered	300	32		
	9		Quenched & Tempered	350	38		
	10		High alloyed steel, and tool steel	Annealed	200	15	
	11		Quenched & Tempered	325	35		
M	12	Stainless steel	Ferritic / Martensitic Annealed	200	15	○	○
	13		Martensitic Quenched & Tempered	240	23		
	14		Austenitic	180	10		
K	15	Grey cast iron	Pearlitic / ferritic	180	10	○	○
	16		Pearlitic (Martensitic)	260	26		
	17	Nodular cast iron	Ferritic	160	3		
	18		Pearlitic	250	25		
	19		Ferritic	130			
20	Malleable cast iron	Pearlitic	230	21			
N	21	Aluminum-wrought alloy	Not Curable	60		◎	◎
	22		Curable Hardened	100		◎	◎
	23	Aluminum-cast, alloyed	≤ 12% Si, Not Curable	75		◎	◎
	24		≤ 12% Si, Curable Hardened	90		◎	◎
	25		> 12% Si, Not Curable	130			
	26	Copper and Copper Alloys (Bronze / Brass)	Cutting Alloys, PB>1%	110			
	27		CuZn, CuSnZn (Brass)	90			
	28		CuSn, lead-free copper and electrolytic copper	100			
	29	Non Metallic Materials	Duroplastic, Fiber Reinforced Plastic				
	30		Rubber, Wood, etc.				
S	31	Heat Resistant Super Alloys	Fe Based Annealed	200	15		
	32		Cured	280	30		
	33		Annealed	250	25		
	34		Cured	350	38		
	35	Cast	320	34			
	36	Titanium Alloys	Pure Titanium	400 Rm		○	○
	37		Alpha + Beta Alloys Hardened	1050 Rm			
H	38	Hardened steel	Hardened	550	55		
	39		Hardened	630	60		
	40	Chilled Cast Iron	Cast	400	42		
41	Hardened Cast Iron	Hardened	550	55			



D5405 SERIES

CARBIDE DRILLS



VOLLHARTMETALL-SPIRALBOHRER
Forets carbure, série extra-courte
PUNTE IN METALLO DURO

STUB

EXTRA KURZ
EXTRA-COURTE
EXTRA CORTA

Application : Drilling steels in general, cast steels, cast iron, chilled cast iron, malleable cast iron, non-ferrous heavy metals, non-ferrous light metals, abrasive plastics.

Verwendung : Zum wirtschaftlichen Bohren von Stahl allgemein, Stahlguß, Hart-und Temperguß, Nichteisen Leichtmetallen, abrasiven Kunststoffen.



D1=D2

DIN 6539 CARBIDE 30° h6 h7 118° Bright p.A159

Recommended Toolholder
Plain Shank
HYDRAULIC CHUCK
SHRINK FIT HOLDER
ER COLLET CHUCK

EDP No.	Drill Diameter			Flute Length			Overall Length		
	D1	L1	L2	D1	L1	L2	D1	L1	L2
D5405010	1.0	6	26	D5405034	3.4	20	52		
D5405011	1.1	7	28	D5405035	3.5	20	52		
D5405012	1.2	8	30	D5405036	3.6	20	52		
D5405013	1.3	8	30	D5405037	3.7	20	52		
D5405014	1.4	9	32	D5405038	3.8	22	55		
D5405015	1.5	9	32	D5405039	3.9	22	55		
D5405016	1.6	10	34	D5405040	4.0	22	55		
D5405017	1.7	10	34	D5405041	4.1	22	55		
D5405018	1.8	11	36	D5405042	4.2	22	55		
D5405019	1.9	11	36	D5405043	4.3	24	58		
D5405020	2.0	12	38	D5405044	4.4	24	58		
D5405021	2.1	12	38	D5405045	4.5	24	58		
D5405022	2.2	13	40	D5405046	4.6	24	58		
D5405023	2.3	13	40	D5405047	4.7	24	58		
D5405024	2.4	14	43	D5405048	4.8	26	62		
D5405025	2.5	14	43	D5405049	4.9	26	62		
D5405026	2.6	14	43	D5405050	5.0	26	62		
D5405027	2.7	16	46	D5405051	5.1	26	62		
D5405028	2.8	16	46	D5405052	5.2	26	62		
D5405029	2.9	16	46	D5405053	5.3	26	62		
D5405030	3.0	16	46	D5405054	5.4	28	66		
D5405031	3.1	18	49	D5405055	5.5	28	66		
D5405032	3.2	18	49	D5405056	5.6	28	66		
D5405033	3.3	18	49	D5405057	5.7	28	66		

TiN(D6405), TiCN(DG405) and TiAlN(DH405) are available on your request.

NEXT PAGE

◎ : Excellent ○ : Good

ISO	P										M				K					
	Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel		Stainless steel		Grey cast iron	Nodular cast iron		Malleable cast iron		
Material Description	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
VDI 3323																				
HRc	13	25	28	32	30	10	29	32	38	15	35	15	23	10	10	26	3	25	21	
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommended	◎	○				○						○			○					

ISO	N										S					H					
	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)		Non Metallic Materials			Heat Resistant Super Alloys			Titanium Alloys		Hardened steel	Chilled Cast Iron	Hardened Cast Iron			
Material Description	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
VDI 3323																					
HRc	60	100	75	90	130	110	90	100			15	30	25	38	34	400Rm	1050Rm	55	60	42	55
HB	60	100	75	90	130	110	90	100			200	280	250	350	320			550	630	400	550
Recommended	◎	◎	◎	◎												○					

YG GENERAL CARBIDE DRILLS

D5405 SERIES

CARBIDE DRILLS



- VOLLHARTMETALL-SPIRALBOHRER
- Forets carbure, série extra-courte
- PUNTE IN METALLO DURO

STUB

EXTRA KURZ
EXTRA-COURTE
EXTRA CORTA

Application : Drilling steels in general, cast steels, cast iron, chilled cast iron, malleable cast iron, non-ferrous heavy metals, non-ferrous light metals, abrasive plastics.

Verwendung : Zum wirtschaftlichen Bohren von Stahl allgemein, Stahlguß, Hart-und Temperguß, Nichteisen Leichtmetallen, abrasiven Kunststoffen.



D1=D2

DIN 6539 CARBIDE 30° h6 h7 118° Bright p.A159

Recommended Toolholder: Plain Shank, HYDRAULIC CHUCK, SHRINK FIT HOLDER, ER COLLET CHUCK

Unit : mm

EDP No.	Drill Diameter	Flute Length	Overall Length
	D1	L1	L2
D5405058	5.8	28	66
D5405059	5.9	28	66
D5405060	6.0	28	66
D5405061	6.1	31	70
D5405062	6.2	31	70
D5405063	6.3	31	70
D5405064	6.4	31	70
D5405065	6.5	31	70
D5405066	6.6	31	70
D5405067	6.7	31	70
D5405068	6.8	34	74
D5405069	6.9	34	74
D5405070	7.0	34	74
D5405071	7.1	34	74
D5405072	7.2	34	74
D5405073	7.3	34	74
D5405074	7.4	34	74
D5405075	7.5	34	74
D5405076	7.6	37	79
D5405077	7.7	37	79
D5405078	7.8	37	79
D5405079	7.9	37	79
D5405080	8.0	37	79
D5405081	8.1	37	79
D5405082	8.2	37	79

EDP No.	Drill Diameter	Flute Length	Overall Length
	D1	L1	L2
D5405083	8.3	37	79
D5405084	8.4	37	79
D5405085	8.5	37	79
D5405086	8.6	40	84
D5405087	8.7	40	84
D5405088	8.8	40	84
D5405089	8.9	40	84
D5405090	9.0	40	84
D5405091	9.1	40	84
D5405092	9.2	40	84
D5405093	9.3	40	84
D5405094	9.4	40	84
D5405095	9.5	40	84
D5405096	9.6	43	89
D5405097	9.7	43	89
D5405098	9.8	43	89
D5405099	9.9	43	89
D5405100	10.0	43	89
D5405102	10.2	43	89
D5405105	10.5	43	89
D5405110	11.0	47	95
D5405115	11.5	47	95
D5405120	12.0	51	102
D5405130	13.0	51	102

TiN(D6405), TiCN(DG405) and TiAlN(DH405) are available on your request.

◎ : Excellent ○ : Good

ISO Material Description	P										M				K					
	Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel		Stainless steel		Grey cast iron		Nodular cast iron		Malleable cast iron	
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc	13	25	28	32	30	10	29	32	38	15	35	15	23	10	10	26	3	25	21	21
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommended	◎	○				○				○					○					

ISO Material Description	N										S						H				
	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys						Titanium Alloys		Hardened steel	Chilled Cast Iron	Hardened Cast Iron
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
HRc	15	30	25	38	34	15	30	25	38	34	15	30	25	38	34	55	60	42	42	55	55
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400	550
Recommended	◎	◎	◎	◎												○					

YG GENERAL CARBIDE DRILLS

D5407 SERIES

CARBIDE DRILLS



- VOLLHARTMETALL-SPIRALBOHRER
- Forets carbure, série courte
- PUNTE IN METALLO DURO

JOBBER

KURZ
COURTE
CORTA

Application : Drilling steels in general, cast steels, cast iron, chilled cast iron, malleable cast iron, non-ferrous heavy metals, non-ferrous light metals, abrasive plastics.

Verwendung : Zum wirtschaftlichen Bohren von Stahl allgemein, Stahlguß, Hart-und Temperguß, Nichteisen Leichtmetallen, abrasiven Kunststoffen.



D1=D2

DIN 338 CARBIDE 30° h6 h7 118° Bright p.A159

Recommended Toolholder: Plain Shank, HYDRAULIC CHUCK, SHRINK FIT HOLDER, ER COLLET CHUCK

Unit : mm

EDP No.	Drill Diameter	Flute Length	Overall Length
	D1	L1	L2
D5407010	1.0	12	34
D5407011	1.1	14	36
D5407012	1.2	16	38
D5407013	1.3	16	38
D5407014	1.4	18	40
D5407015	1.5	18	40
D5407016	1.6	20	43
D5407017	1.7	20	43
D5407018	1.8	22	46
D5407019	1.9	22	46
D5407020	2.0	24	49
D5407021	2.1	24	49
D5407022	2.2	27	53
D5407023	2.3	27	53
D5407024	2.4	30	57
D5407025	2.5	30	57
D5407026	2.6	30	57
D5407027	2.7	33	61
D5407028	2.8	33	61
D5407029	2.9	33	61
D5407030	3.0	33	61
D5407031	3.1	36	65

EDP No.	Drill Diameter	Flute Length	Overall Length
	D1	L1	L2
D5407032	3.2	36	65
D5407033	3.3	36	65
D5407034	3.4	39	70
D5407035	3.5	39	70
D5407036	3.6	39	70
D5407037	3.7	39	70
D5407038	3.8	43	75
D5407039	3.9	43	75
D5407040	4.0	43	75
D5407041	4.1	43	75
D5407042	4.2	43	75
D5407043	4.3	47	80
D5407044	4.4	47	80
D5407045	4.5	47	80
D5407046	4.6	47	80
D5407047	4.7	47	80
D5407048	4.8	52	86
D5407049	4.9	52	86
D5407050	5.0	52	86
D5407051	5.1	52	86
D5407052	5.2	52	86
D5407053	5.3	52	86

TiN(D6407), TiCN(DG407) and TiAlN(DH407) are available on your request.

▶ NEXT PAGE

ISO Material Description	P										M				K					
	Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel		Stainless steel		Grey cast iron		Nodular cast iron		Malleable cast iron	
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc	13	25	28	32	30	10	29	32	38	15	35	15	23	10	10	26	3	25	21	21
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommended	◎	○				○				○					○					

ISO Material Description	N										S						H				
	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys						Titanium Alloys		Hardened steel	Chilled Cast Iron	Hardened Cast Iron
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
HRc	15	30	25	38	34	15	30	25	38	34	15	30	25	38	34	55	60	42	42	55	55
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400	550
Recommended	◎	◎	◎	◎												○					

GENERAL CARBIDE DRILLS

D5407 SERIES


CARBIDE DRILLS

VOLLHARTMETALL-SPIRALBOHRER
Forets carbure, série courte
MPUNTE IN METALLO DURO

JOBBER
KURZ
COURTE
CORTA

► **Application** : Drilling steels in general, cast steels, cast iron, chilled cast iron, malleable cast iron, non-ferrous heavy metals, non-ferrous light metals, abrasive plastics.

► **Verwendung** : Zum wirtschaftlichen Bohren von Stahl allgemein, Stahlguß, Hart-und Temperguß, Nichteisen Leichtmetallen, abrasiven Kunststoffen.



D1=D2

DIN 338 **CARBIDE** **30°** **h6** **h7** **118°** **Bright** p.A159

Recommended Toolholder

- Plain Shank
- HYDRAULIC CHUCK
- SHRINK FIT HOLDER
- ER COLLET CHUCK

Unit : mm

EDP No.	Drill Diameter	Flute Length	Overall Length	EDP No.	Drill Diameter	Flute Length	Overall Length
	D1	L1	L2		D1	L1	L2
D5407054	5.4	57	93	D5407070	7.0	69	109
D5407055	5.5	57	93	D5407075	7.5	69	109
D5407056	5.6	57	93	D5407080	8.0	75	117
D5407057	5.7	57	93	D5407085	8.5	75	117
D5407058	5.8	57	93	D5407090	9.0	81	125
D5407059	5.9	57	93	D5407095	9.5	81	125
D5407060	6.0	57	93	D5407100	10.0	87	133
D5407061	6.1	63	101	D5407102	10.2	87	133
D5407062	6.2	63	101	D5407105	10.5	87	133
D5407063	6.3	63	101	D5407110	11.0	94	142
D5407064	6.4	63	101	D5407115	11.5	94	142
D5407065	6.5	63	101	D5407120	12.0	101	151
D5407068	6.8	69	109	D5407130	13.0	101	151

► TiN(D6407), TiCN(DG407) and TiAlN(DH407) are available on your request.

◎ : Excellent ○ : Good

ISO	P										M					K				
	Non-alloy steel					Low alloy steel					High alloyed steel, and tool steel		Stainless steel			Grey cast iron		Nodular cast iron		Malleable cast iron
VDI 3323	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
HRc	125	130	135	140	145	150	155	160	165	170	175	180	185	190	195	200	205	210	215	220
HB	125	190	250	270	300	180	275	300	350	200	325	200	240	180	180	260	160	250	130	230
Recommended	◎	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

ISO	N										S							H			
	Aluminum-wrought alloy		Aluminum-cast, alloyed			Copper and Copper Alloys (Bronze / Brass)			Non Metallic Materials		Heat Resistant Super Alloys					Titanium Alloys		Hardened steel	Chilled Cast Iron	Hardened Cast Iron	
VDI 3323	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
HRc	60	100	75	90	130	110	90	100			15	30	25	38	34	55	60	55	60	42	55
HB	60	100	75	90	130	110	90	100			200	280	250	350	320	400Rm	1050Rm	550	630	400	550
Recommended	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎	◎

GENERAL CARBIDE DRILLS

D5405, D5407 SERIES GENERAL CARBIDE DRILLS


RECOMMENDED CUTTING CONDITIONS
EMPFOHLENE SCHNEIDPARAMETER

Vc = m/min.
 RPM = rev./min.
 FEED = mm/rev.

ISO	VDI 3323	Material Description	Vc	Parameter	Drill Diameter (mm)		Vc	Parameter	Drill Diameter (mm)							
					1.0	2.0			3.0	4.0	5.0	6.0	8.0	10.0	12.0	13.0
P	1	Non-alloy steel	55	RPM	17510	8750	70	RPM	7430	5570	4460	3710	2790	2230	1860	1710
			FEED	0.02-0.03	0.02-0.04	FEED		0.03-0.05	0.03-0.06	0.04-0.07	0.05-0.08	0.07-0.10	0.08-0.12	0.10-0.14	0.12-0.16	
	2	45	RPM	14320	7160	60	RPM	6370	4770	3820	3180	2390	1910	1590	1470	
M	12	Stainless steel	15	RPM	4770	2390	25	RPM	2650	1990	1590	1330	990	800	660	610
			FEED	0.01-0.02	0.01-0.03	FEED		0.02-0.04	0.02-0.05	0.03-0.06	0.04-0.07	0.06-0.09	0.07-0.11	0.08-0.12	0.09-0.13	
	6	35	RPM	11140	5570	50	RPM	5310	3980	3180	2650	1990	1590	1330	1220	
K	15	Grey cast iron	25	RPM	7960	3980	45	RPM	4770	3580	2860	2390	1790	1430	1190	1100
			FEED	0.03-0.04	0.03-0.05	FEED		0.04-0.06	0.04-0.07	0.05-0.08	0.06-0.09	0.09-0.12	0.12-0.16	0.14-0.18	0.16-0.20	
	21	100	RPM	31830	15920	140	RPM	14850	11140	8910	7430	5570	4460	3710	3430	
N	22	Aluminum-wrought alloy	90	RPM	28650	14320	120	RPM	12730	9550	7640	6370	4770	3820	3180	2940
			FEED	0.04-0.05	0.04-0.06	FEED		0.05-0.07	0.05-0.08	0.06-0.09	0.08-0.11	0.12-0.15	0.15-0.19	0.19-0.23	0.21-0.25	
	23	70	RPM	22280	11140	100	RPM	10610	7960	6370	5310	3980	3180	2650	2450	
S	36	Titanium Alloys	10	RPM	19100	9550	80	RPM	8490	6370	5090	4240	3180	2550	2120	1960
			FEED	0.04-0.05	0.04-0.06	FEED		0.05-0.07	0.05-0.08	0.06-0.09	0.08-0.11	0.12-0.15	0.15-0.19	0.19-0.23	0.21-0.25	
	24	60	RPM	3180	1590	20	RPM	2120	1590	1270	1060	800	640	530	490	



Global Cutting Tool Leader **YG-1**



HOLEMAKING